1/2 HP AC CHAIN DRIVE WI-FI® GARAGE DOOR OPENER



INCLUDED ACCESSORIES:

DOOR CONTROL BUTTON Controls the opener and the opener's lights.



883LM

1-BUTTON REMOTE CONTROL Operates a single opener or



RELIABLE

1/2 HP AC MOTOR IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

CHAIN DRIVE SYSTEM FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

WARRANTY 4-YEAR MOTOR, 1-YEAR PARTS.

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

MYQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

SECURITY+ 2.0° SENDS A NEW CODE WITH EVERY REMOTE CLICK.


POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

POWERFUL ADD-ONS:

MVQ HOME BRIDGE





8191

MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access



374UT

REMOTE LIGHT CONTROL

Plug in any lamp to this device to control it with a smartphone or garage remote.



REMOTE LIGHT SWITCH

Replaces an existing wall switch to control home lighting with a smartphone or garage remote.





GARAGE DOOR AND GATE MONITOR

Monitors and closes up to 4 garage doors from any room in the house



8 1 6 4 W

rabled accessory automaticals and away from home requires an Apple TV® with

MASTERFUL ENGINEERING.

MOTOR

- -1/2 Horsepower AC
- -1,625 RPM
- -Automatic Thermal

-Permanent Lubrication

Protection

POWER

- -120V AC
 - -60 Hz Voltage -6A Current Rating
 - -UL* Listed
 - -4' Power Cord (3-Prong)

MECHANICS



- -Steel Chassis, T-Rail and Trolley
- -Full Chain Drive Mechanism (16:1 Gear Reduction and Adjustable Door Arm)
- -Auto-Force Adjustment for Changing Weather and
- **Environmental Conditions** - Electronic Limits for Easy Setup
- -AC Wi-Fi Logic Board with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050ACTWF)

= 10 New



DIMENSIONS

Rail Options	7'	8,	10'
Installed Length	124"	136*	160"
Max. Opening	7'6"	8'6"	10'6"
Handraam Classon	oo Boo	olenda /	2003

SPEED

STANDARD SPECS.

SECURITY+ 2.0° RADIO CONTROLS

1-Button Remote Control (891LM)

Operating Range: ~200

Operating Temperature: -30°F to 150°F

- Frequency:
 Remote Control: 310, 315 and
 390 MHz Tri-Band
- 390 MHz Tri-Band
 Garage Door Opener: Frequency Agile
 on 310, 315 and 390 MHz
 Security+ 2.0 Anti-Burglary Coding

SECURITY+ 2.0

- ENCRYPTED CONTROLS

 Door Control Button (883LMW)

 Program Remote Controls
- Turn Opener Lights On and Off
- Easy Wi-Fi Setup

MvQ° RADIO



- Provides 2-way communication
- from garage door opener and MyQ Accessories. Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

LIGHTING

- Max. 1 100-Watt

Lightbulb Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

HOMELINK® COMPATIBLE

(VERSION 4.0 OR HIGHER*)
*May require an external adapter
depending on the model and year of your vehicle, Visit HomeLink.com for additional information.